



P/N:	
LENGTH	TOLERANCE
0.25M	±15MM
0.5M	±20MM
0.7M	±20MM
1M	±20MM
1.5M	±30MM
2M	±30MM
3M	±45MM
4M	±60MM
5M	±75MM
7M	±100MM
10M	±150MM
15M	±200MM
20M	±250MM
25M	±300MM
30M	±350MM
50M	±750MM

P1					P2
WH 1		1	WH		
OG 2		2	OG		
RE 3		3	RD		
GN 6		6	GN		
BU 4		4	BU		
WH 5		5	WH		
WH 7		7	WH		
BN 8		8	BN		
SHELL	BRAID			SHELL	

NOTES:
1:100% short,open and miss wire test.
2:CABLE MARKING:CAT6A SSTP (S/FTP) LSZH 500MHz 4PAIRS
STRANDED AWG26 RoHS COMPLIANT
3:RoHS compliant.

③	OUTER MOLDED	75P PVC,THE COLOR ACCORDING TO CABLE COLOR	0.048	KG
②	CONNECTOR	STP 8P8C RED TRANSPARENT PC HEAD, THE PIN FOR GOLD PLATED FU",NICKEL-PLATED SHELL.	2	PCS
①	CABLE	CAT.6A S/FTP 27AWG(7/0.13BC*1P+AL-FOIL)*4+B(16/5/0.12) AL-MG JACKET:LSZH/ OD:6.0+/-0.2mm	L	M
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT