16/24-Port 10/100Mbps Rackmount Switch

MODEL: TL-SF1016/TL-SF1024



Specifications

Hardware Specifications & Performance

Product Picture			
Model		TL-SF1016	TL-SF1024
Hardware Features	Standards and Protocols	IEEE 802i, IEEE 802.3u, IEEE 802.3x	
	Interface	16 10/100Mbps RJ45 Ports Auto Negotiation/Auto MDI/MDIX	24 10/100Mbps RJ45 Ports Auto Negotiation/Auto MDI/MDIX
	Forwarding Mode	Store-and-Forward	
	Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)	
	Power Supply	100-240VAC, 50/60Hz	
	Green Technology	Yes	
	Dimensions	17.3*7.1*1.7 in. (440*180*44 mm)	
	Fanless	Yes	
Performance	Switching Capacity	3.2Gbps	4.8Gbps
	Packet Forwarding Rate	2.38Mpps	3.57Mpps
	MAC Address Table	8K	
	Jumbo Frame	2KB	
	Max Power Consumption	2.06W (220V/50Hz)	3.19W (220V/50Hz)
	Max Heat Dissipation	7.03 BTU/h	10.88 BTU/h
Certification		CE, FCC, RoHS	
Environment	Operating Temperature	0°C~40°C (32°F~104°F)	
	Storage Temperature	-40°C~70°C (-40°F~158°F)	
	Operating Humidity	10%~90%RH non-condensing	
	Storage Humidity	5%~90%RH non-condensing	
Ordering Information		16-Port 10/100Mbps Rackmount Switch	24-Port 10/100Mbps Rackmount Switch