



Pharos CPE Series

Dedicated Long-Range Outdoor
Wireless Networking Solution

CPE210/CPE510

Highlights

- Selectable bandwidth of 5/10/20/40 MHz
- Adjustable transmission power by 1 dBm
- Broad operating frequency channels ensure less wireless interference
- Passive PoE Adapter supports up to 60 meter¹ (200 feet) Power over Ethernet deployment
- TP-Link Pharos MAXtream (Time-Division-Multiple-Access) technology improves product throughput, capacity and latency performance, ideal for PtMP applications
- Centralized Management System – Pharos Control



¹ Power supply distances are based on test results under normal usage conditions. Actual power supply distance will vary as a result of 1) AP status, including transmit power, connected devices and network traffic and 2) cable properties, including type and texture.

Specification

Features & Performance

Model		CPE210	CPE510
Name		2.4 GHz 300 Mbps 9 dBi Outdoor CPE	5 GHz 300 Mbps 13 dBi Outdoor CPE
Package Contents		Outdoor CPE 24 V Passive PoE Adapter AC Power Cord Mounting Kits Quick Installation Guide	
Hardware Feature	Processor	Qualcomm 650 MHz CPU, MIPS 24 Kc	Qualcomm 560 MHz CPU, MIPS 74 Kc
	Memory	64 MB DDR2 RAM, 8 MB Flash	
	Antenna Gain	9 dBi	13 dBi
	Beamwidth	65° (Azimuth)/40° (Elevation)	45° (Azimuth)/45° (Elevation)
	Interfaces	1 10/100 Mbps Shielded Ethernet Port (LAN/POE) 1 Grounding Terminal 1 Reset Button	1 10/100 Mbps Shielded Ethernet Port (LAN/POE) 1 Grounding Terminal 1 Reset Button
	Power Supply	24 VDC/0.25 A Passive PoE (+4,5 pins; -7,8 pins)	
	Dimensions (L x W x H)	224 × 79 × 60 mm	224 × 79 × 60 mm
	Protection ²	15 kV ESD Protection 6 kV Lightning Protection	
	Enclosure	Material: Outdoor ASA stabilized plastic Weatherproof: IPX5 water and dust proof design	

²Protection against lightning and electro-static discharge may be achieved through proper product setup, grounding and cable shielding. Refer to the instruction manual and consult an IT professional to assist with setting up this product.

Specification

Features & Performance

Model		CPE210	CPE510
Name		2.4 GHz 300 Mbps 9 dBi Outdoor CPE	5 GHz 300 Mbps 13 dBi Outdoor CPE
Wireless Features	Wireless Standards	IEEE 802.11 b/g/n	IEEE 802.11 a/n
	Proprietary Protocol	TDMA Mode (with Pharos MAXstream enabled)	
	Frequency ³	2.4-2.483 GHz	5.15-5.85 GHz
	Wireless Speed ⁴	Up to 300 Mbps (40 MHz, Dynamic) Up to 144.4 Mbps (20 MHz, Dynamic) Up to 72.2 Mbps (10 MHz, Dynamic) Up to 36.1 Mbps (5 MHz, Dynamic)	
	Maximum Transmit Power ⁵	25 dBm (Adjustable power by 1 dBm)	26 dBm (Adjustable power by 1 dBm)
Software Feature	Operation Mode	AP/Client/Bridge/Repeater/AP Router/AP Client Router (WISP Client)	
	Network Configurations	WAN: Static/Dynamic/PPPoE/L2TP/PPTP LAN: Static/Dynamic/DHCP IPv6 Forwarding: ALG/UPnP/Virtual Server/Port Trigger Security: SPI Firewall/ Ping Forbidden/DoS Protection Access Control Static Routing Bandwidth Control IP & MAC Binding	

³ Available operating frequency may vary depending on the limitaion of the countries or regions in which the device is used.

⁴ Maximum wireless transmission rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless transmission rate will vary as a result of:

- 1) environmental factors, including building materials, physical objects and obstacles,
- 2) network conditions, including local interference, volume and density of traffic, product location, network complexity, and network overhead and
- 3) client limitations, including rated performance, location, connection quality, and client condition.

⁵ Maximum transmit power is limited by local regulatory settings.

Specification

Features & Performance

Model		CPE210	CPE510
Name		2.4 GHz 300 Mbps 9 dBi/12 dBi Outdoor CPE	5 GHz 300 Mbps 13 dBi Outdoor CPE
Software Feature	Wireless Configurations	Pharos MAXtream TDMA Technology Long Range PtP Selectable Channel Width: 5/10/20/40 MHz Auto Channel Selection Transmit Power Control Dynamic Frequency Selection (DFS) WDS Enable/Disable Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption 64/128/152-bit WEP Encryption SSID Broadcast Enable/Disable Multi-SSID with VLAN Tagging (AP mode only) Distance/ACK Timeout Setting Wireless MAC Address Filter Wireless Advanced: Beacon Inteval/RTS Threshold/Fragmentation Threshold/DTIM Inteval/AP Isolation/Short GI/Wi-Fi Multimedia	
	Management	Discovery and Remote Management via Pharos Control application HTTP/HTTPS Web-based management System Log SNMP Agent (v2c) Ping Watch Dog Dynamic DDNS SSH Server	
	System Tools	Indicators: Signal Strength/Noise/Transmit CCQ/CPU/Memory Monitors: Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP Spectrum Analysis Speed Test Ping Traceroute Antenna Alignment	

Specification

Features & Performance

Model		CPE210	CPE510
Name		2.4 GHz 300 Mbps 9 dBi/12 dBi Outdoor CPE	5 GHz 300 Mbps 13 dBi Outdoor CPE
Software Feature	System-level Optimizations	IGMP Snooping/Proxy for multicast applications	
	System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux. Note: We recommend you to use one of following Web browsers for better experience: Google Chrome, Safari, Firefox. IE browsers are not recommended.	
Others	Certification	CE, FCC, RoHS, IPX5	
	Environment	Operating Temperature: -40 °C~70 °C (-40 °F~158 °F) Storage Temperature: -40 °C~70 °C (-40 °F~158 °F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing	