

Specifications

	PE0224SA	PE0224SB	PE0224SG
Electrical			
Nominal Input Voltage	100-120 VAC	100-240 VAC	100-240 VAC
Maximum Input Current	20A (Max); 16A (UL de-rated)	20A (Max); 16A (UL de-rated)	16A (Max)
Input Frequency	50-60 Hz	50-60 Hz	50-60 Hz
Input Connection	For A plug: NEMA L5-20P; For A2 plug: NEMA 5-20P	NEMA L6-20P	IEC 60320 C20
Input Power	2400VA (Max); 1920VA (UL de-rated)	4800VA (Max); 3840VA (UL de-rated)	3840VA (Max)
Outlet Type	(24) NEMA 5-20R	(22) IEC 60320 C13, (2) IEC 60320 C19	(22) IEC 60320 C13, (2) IEC 60320 C19
Maximum Output Current (Outlet)	20A (Max); 16A (UL de-rated)	C13: 15A(Max); 12A(UL de-rated) C19: 20A(Max); 16A(UL de-rated)	C13: 10A (Max) C19: 16A (Max)
Maximum Output Current (Bank)	20A (Max); 16A (UL de-rated)	20A (Max); 16A (UL de-rated)	16A (Max)
Maximum Output Current (Total)	20A (Max); 16A (UL de-rated)	20A (Max); 16A (UL de-rated)	16A (Max)
OPD (Overcurrent Protection Device)	Yes	Yes	Yes
Environmental			
Temperature (Operating / Storage)	0 – 40°C / -20 – 60°C	0 – 40°C / -20 – 60°C	0 – 40°C / -20 – 60°C
Elevation (Operating / Storage)	3000m	3000m	3000m
Physical Properties			
Dimensions (L x W x H)	96.71 x 4.44 x 6.00 cm (38.07 x 1.75 x 2.36 in.)	108.71 x 4.44 x 6.00 cm (42.80 x 1.75 x 2.36 in.)	108.71 x 4.44 x 6.00 cm (42.80 x 1.75 x 2.36 in.)
Weight	1.40 kg (3.08 lb)	1.40 kg (3.08 lb)	1.40 kg (3.08 lb)
Power Cord Length	10ft (12#)	10ft (12#)	10ft (3x1.5mm ²)
Compliance			
EMC Verification	FCC Class A	FCC Class A	CE Class A
Safety Verification	By Request	By Request	CE,LVD

PE0224SA Front View

