

Specifications

	PE1118SA	PE1118SG
Electrical		
Nominal Input Voltage	100 - 120 VAC	100 - 240 VAC
Maximum Input Current	15A (Max); 12A (UL de-rated)	10A (Max)
Input Frequency	50 - 60 Hz	50 - 60 Hz
Input Connection	NEMA 5-15P	IEC 60320 C14
Input Power	1800VA (Max); 1440VA (UL de-rated)	2400VA (Max)
Outlet Type	(18) NEMA 5-15R	(18) IEC 60320 C13
Maximum Output Current (Outlet)	15A (Max); 12A (UL de-rated); 10A (PSE)	10A (Max)
Maximum Output Current (Bank)	15A (Max); 12A (UL de-rated); 10A (PSE)	10A (Max)
Maximum Output Current (Total)	15A (Max); 12A (UL de-rated); 10A (PSE)	10A (Max)
OPD(Overcurrent Protection Device)	Yes	Yes
Environmental		
Temperature (Operating / Storage)	0 – 40 °C / -20 – 60 °C	0 – 40 °C / -20 – 60 °C
Elevation (Operating / Storage)	3000 m	3000 m
Physical Properties		
Dimensions (L x W x H)	44.00 x 4.44 x 8.85 cm (17.32 x 1.75 x 3.48 in.)	44.00 x 4.44 x 8.85 cm (17.32 x 1.75 x 3.48 in.)
Weight	1.30 kg (2.86 lb)	1.30 kg (2.86 lb)
Power Cord Length	10ft (14#)	10ft (3×1.0mm ²)
Compliance		
EMC Verification	FCC Class A	CE Class A
Safety Verification	Upon Request	CE, LVD